

# Enhancing Renewable Grid Stability Using Machine Learning for Power Quality: A Comprehensive Research

**Vaibhav Saini**

M. Tech. in Electrical Engineering, CBS Group of Institutions, Jhajjar, Haryana.

**Nisar**

A.P Electrical Department, CBS Group of Institutions, Jhajjar, Haryana.

---

## ABSTRACT

The integration of renewable energy into power systems introduces variability and intermittency, challenging power quality and grid stability. This study investigates machine learning-based methods for improving power quality in renewable energy integrated systems. Models such as Linear Regression, Random Forest, and LSTM are applied for energy forecasting, optimization, and predictive maintenance. Results indicate that ML-driven approaches significantly enhance forecast accuracy, reduce power losses, improve load served, and stabilize voltage and frequency. Integration with IoT sensors and smart grid infrastructure enables real-time adaptive control. The findings demonstrate that machine learning provides a robust, scalable solution for reliable and efficient renewable energy management.

**Keywords:** *Machine Learning, Power Quality, Renewable Energy, Predictive Maintenance.*

## I. INTRODUCTION

The global transition towards renewable energy sources has become a cornerstone in addressing the pressing challenges of climate change, energy security, and sustainable development. Over the past two decades, the integration of renewable energy technologies, such as solar photovoltaic (PV) systems, wind turbines, and hybrid renewable energy systems (HRES), has significantly increased within power grids worldwide. Unlike conventional energy sources, renewable energy systems are inherently variable, intermittent, and weather-dependent, which poses substantial challenges to maintaining power quality and system stability. Power quality, defined as the ability of the electrical system to deliver steady voltage and frequency within prescribed limits, is essential for ensuring the safe and efficient operation of electrical equipment. Deviations in voltage, frequency fluctuations, harmonics, flicker, and reactive power imbalances are common issues encountered in renewable-integrated grids. These disturbances can compromise sensitive industrial loads, reduce equipment lifespan, and even lead to grid instability or blackouts. Conventional methods for improving power quality, such as the installation of capacitors, filters, static compensators, and synchronous condensers, have proven effective in traditional grids but are often inadequate in highly dynamic renewable environments. As renewable penetration grows, there is a pressing need for advanced control strategies and intelligent management systems that can adapt to rapid changes in generation and load, optimize energy dispatch, and maintain voltage and frequency stability. Machine learning (ML) and artificial intelligence (AI) techniques have emerged as promising tools to address these challenges, offering predictive, adaptive, and data-driven solutions that significantly enhance power quality in renewable energy integrated systems.

Machine learning-based methods provide a paradigm shift in how power systems can be monitored, controlled, and optimized. Unlike conventional rule-based approaches, ML models learn patterns from historical and real-time data to forecast energy generation, predict load variations, detect anomalies, and optimize control actions autonomously. Forecasting plays a crucial role in power quality management, as the intermittent nature of renewable sources such as solar and wind can lead to sudden voltage drops or

frequency deviations if not anticipated properly. Advanced ML models, including artificial neural networks (ANNs), support vector regression (SVR), long short-term memory (LSTM) networks, and random forests, have demonstrated high accuracy in predicting solar irradiance, wind speed, and short-term energy demand. By leveraging these predictions, energy management systems can dynamically adjust dispatch from renewable sources, energy storage, and backup grids to stabilize voltage and frequency. In hybrid renewable energy systems, machine learning algorithms can optimize the operation of multiple energy sources in coordination with battery storage systems, ensuring maximum energy utilization while minimizing power losses. Reinforcement learning-based approaches further enhance system adaptability by continuously learning optimal control policies through interaction with the grid environment. This allows for real-time corrective actions in response to unforeseen disturbances or fluctuations in renewable generation, thereby maintaining power quality within acceptable limits. Furthermore, ML-based models support the integration of decentralized energy resources, enabling peer-to-peer energy trading among prosumers, which not only reduces dependency on centralized generation but also promotes local voltage and frequency stabilization.

Predictive maintenance and fault detection represent another critical area where machine learning enhances power quality in renewable energy integrated systems. Renewable energy components such as wind turbine generators, photovoltaic panels, inverters, and battery storage units are susceptible to performance degradation and faults, which can result in voltage sags, power interruptions, and reactive power imbalances if not addressed promptly. AI-based predictive maintenance leverages historical performance data, real-time sensor measurements, and advanced ML models to detect early signs of equipment deterioration, forecast potential failures, and schedule maintenance proactively. Studies indicate that AI-driven predictive maintenance can reduce unplanned downtime by 30–35% and increase energy output by approximately 8–10%, thereby contributing to more stable and reliable grid operation. Additionally, the integration of ML with smart grid infrastructure, Internet of Things (IoT) devices, and big data analytics facilitates continuous monitoring and adaptive control. IoT-enabled sensors provide high-resolution data on voltage, current, temperature, wind speed, and solar irradiance, which ML algorithms analyze to optimize reactive power compensation, voltage regulation, and load balancing. Optimization algorithms, such as genetic algorithms, particle swarm optimization, and hybrid AI methods, are employed to determine the best configuration of system parameters, energy storage utilization, and load scheduling, minimizing power losses and maintaining power quality. Moreover, these AI-enabled approaches improve forecast accuracy from approximately 65% using conventional methods to over 90%, enhance energy utilization, reduce battery curtailment, and increase operational efficiency of renewable systems. Consequently, machine learning has become a vital enabler for modern power systems, providing intelligent, scalable, and adaptive solutions to address the complexities of renewable energy integration while maintaining high power quality, grid reliability, and system resilience.

## II. RESEARCH BACKGROUND

**Ram et al. (2026)** were reported to have presented a study on the design of a proportional-integral-derivative (PID) controller for a renewable energy (RE) integrated power system employing model order reduction (MOR). They were described to have validated their method using an 11th-order RE-integrated power system test case from the literature. The 11th-order system model was reportedly reduced to a 2nd-order model through a combination of Pade approximation (PA) and direct truncation (DT), referred to as the PA-DT method. Subsequently, the grey wolf optimization (GWO) technique was employed by the authors to determine the optimal PID parameters for the reduced-order model, which they then applied directly to the high-order system. It was noted that the proposed approach was considered novel, as no

prior publications had reportedly combined PA-DT MOR with PID design for RE integrated systems at that stage. The efficacy of the method was claimed to be demonstrated through time and frequency response analyses, alongside time domain specifications, performance error indices, and supporting statistical analyses.

**Dashti and Bagriyanik (2026)** were reported to have highlighted that modern power systems had become increasingly complex and dynamic due to the extensive integration of renewable energy sources, which had heightened the risk of transient events. They had identified switching over-voltages (SOVs) as a major threat to system reliability, capable of causing insulation failure and equipment damage, thereby prompting an in-depth examination of their management. Their review was said to have synthesized the existing literature on SOVs, encompassing foundational studies, industry standards, and recent research, to reveal the underlying causes, challenges, and evolving mitigation strategies. The authors were described as having traced a clear progression from traditional surge arresters to contemporary methods like synchronous switching, noting a shift toward intelligent systems leveraging artificial intelligence for real-time detection, classification, and control. They concluded that effective mitigation of SOVs in sustainable power systems required a paradigm shift to adaptive, intelligent strategies, and they emphasized the necessity for future research focusing on standardized modeling, AI applications for renewable integration, and the implications of emerging grid technologies.

**Kaewpasuk et al. (2025)** had investigated the challenges posed by the increasing integration of renewable energy sources (RESs), particularly solar photovoltaic (PV) systems, on power system operations, noting that such penetration had introduced considerable uncertainty that compromised traditional scheduling models and system reliability. They had proposed a Fuzzy Unit Commitment Model (FUCM) to manage uncertainties in load demand, solar PV generation, and spinning reserve requirements by employing fuzzy linear programming techniques. In their approach, uncertain constraints were reformulated using triangular membership functions and incorporated into a mixed-integer linear programming (MILP) framework. The model's performance had been validated through two case studies: a 30-generator test system and a national-scale system in Thailand with 171 generators across five service zones. Simulation results reportedly indicated that the FUCM had consistently produced stable scheduling solutions within deterministic upper and lower bounds, enhancing reliability metrics such as reduced loss-of-load probability and minimized load deficiency, while maintaining acceptable computational performance. They concluded that the FUCM offered a practical and scalable method for unit commitment planning under uncertainty, contributing to operational stability and economic efficiency, thereby supporting the sustainable management of RES-integrated power systems.

**Ullah et al. (2025)** were reported to have emphasized that the accelerating integration of electric vehicles (EVs) and renewable energy sources (RESs) into contemporary power systems represented a pivotal advancement toward establishing low-carbon, efficient, and resilient energy infrastructures. They had highlighted that central to this transformation was the development of electric vehicle charging stations (EVCSs), which had posed diverse design, control, and operational challenges. Their review was said to have offered a thorough evaluation of EV and RES integration, with a particular focus on EVCS infrastructure, power converter topologies, and system-level coordination. They had conducted a bibliometric analysis of 1,725 Scopus-indexed documents spanning the last two decades using VOSviewer to reveal research trends, thematic clusters, and patterns of collaboration. Concurrently, they had critically examined technical aspects such as grid impacts, energy management models, charging strategies, and communication protocols. The study reportedly categorized EVCS converter architectures and outlined principal selection criteria according to application requirements, with special emphasis

placed on interoperability standards, smart charging frameworks, and the deployment of intelligent, user-centric EVCS systems. Although the field had witnessed rapid growth, they had identified persistent gaps in interdisciplinary innovation and practical implementation of emerging technologies. Ultimately, the authors were said to have proposed future research directions in AI-driven optimization, grid control, hybrid energy storage, and real-time integration strategies, intending to support researchers, engineers, and policymakers in advancing scalable, intelligent, and sustainable EV-RES-powered energy systems.

**Rastgoo et al. (2024)** were reported to have examined the challenges posed by the extensive integration of renewable energies into power systems, noting that the increased number and complexity of time series data created a computationally demanding scenario for system planning. They were said to have proposed a novel deep learning-based time aggregation method to select representative periods for datasets involving multiple variable energy resources. According to the study, the approach leveraged the capabilities of Generative Adversarial Networks (GANs), incorporating Long Short-Term Memory (LSTM) networks in both the generator and discriminator, and included a clustering-specific loss term in the minimax objective to enhance latent space clustering performance. The authors were described as having adaptively fine-tuned the learning rate based on training error to optimize learning performance. Evaluations on two real-world test cases were reportedly conducted, and the results were claimed to demonstrate that the proposed model outperformed conventional and deep learning-based methods, achieving improvements of 38.55–46.14 % in MAPE, 45.75–70.16 % in RMSE, and 65.81–74.58 % in MAE. The study was suggested to have concluded that the method significantly enhanced the tractability and scalability of renewable energy-integrated power system planning, thereby facilitating the integration of renewable energy as a key factor in community net-zero transitions.

**Debbarma et al. (2024)** had indicated that the increasing penetration of variable renewable generation had been expected to reduce system inertia, thereby impairing the conventional frequency regulation capability. They had argued that, as a consequence, maintaining frequency stability would become progressively more challenging with traditional approaches. While they had acknowledged that the integration of renewable sources might jeopardize grid stability, they had also highlighted the opportunities it presented, such as enabling converter-interfaced generators to participate in real-time electricity markets (RTEM) and provide short-term dispatch to minimize load-generation mismatches. The authors had proposed an integrated approach that accommodated a discrete automatic generation control (AGC) system within a regulation mileage framework and an RTEM model to balance generation and consumption. They had assumed a five-minute dispatch trading interval in the RTEM model, which was considered roughly comparable to the discrete AGC system. Moreover, they had equipped the AGC system with a fractional order PID (FOPID) controller, whose parameters were tuned using a novel metaheuristic optimization technique called the Lichtenberg Algorithm (LA). Their proposed framework had been tested in a three-area system under various operating conditions, revealing improvements in the system's dynamic performance. Additionally, they had incorporated an objective function with mileage payment, which had allowed a fair compensation rule for all participating units.

**Alilou et al. (2023)** were reported to have discussed that the global energy revolution had accelerated the adoption of demand-side manageable energy systems, including wind turbines, photovoltaic panels, electric vehicles, and energy storage systems, as a response to the increasing energy crisis and greenhouse gas emissions. They indicated that the performance of renewable energy units and energy storage systems was highly dependent on their control systems, which in turn significantly affected the efficiency of the overall power network. While classical controllers relied on integer-order differentiation and integration, they suggested that fractional-order controllers held substantial potential due to their ability to adjust the

order for improved modeling and system control. Their review was said to have systematically evaluated numerous studies on renewable energy units and energy storage devices, presenting the methods and findings comprehensively. Additionally, they were described to have outlined the mathematical principles underlying fractional-order techniques and categorized existing studies based on different parameters, providing definitions and formulas for fractional-order calculus. They concluded that various numerical analyses demonstrated that fractional-order methods achieved higher accuracy and efficiency in estimating, controlling, and enhancing energy system performance under diverse operational conditions, with average errors significantly lower than those of conventional approaches.

**Rather, Z. H. and Pal B. C. (2023)** had examined the challenges posed by the displacement of conventional synchronous generation by Inverter-Based Resources (IBRs) in Renewable Energy (RE) integrated power systems, highlighting that such integration, due to low or negligible inertia, had led to elevated Rates of Change of Frequency (RoCoF) and worsened frequency nadir and zenith following system disturbances. They had argued that predicting frequency metrics, including nadir and RoCoF immediately after disturbances, could assist grid operators in taking timely preventive or corrective measures, such as faster frequency control, to maintain stable and secure grid operations. The authors had proposed a straightforward analytical method to estimate the disturbance size in a power system post-contingency, which was subsequently used for predicting frequency nadir. This estimation method had utilized active power measurements from a limited number of monitoring nodes and an adaptive bus admittance matrix. They had then employed the estimated disturbance size in a Neural Network-based approach to predict frequency nadir. The effectiveness and accuracy of their approach had been assessed through extensive simulations using the standard IEEE 39-bus system and the real-life Gujarat power system, considering various disturbance sizes, types, and locations in DIGSILENT PowerFactory.

**Al-Shetwi (2022)** was reported to have examined the continuous growth in global energy demand and its associated environmental impacts, highlighting their significant role in driving the sustainable and green energy transition. The study indicated that the electrical power sector remained a major contributor to carbon dioxide emissions, and therefore, the integration of renewable energy (RE) into the power grid had attracted considerable economic, environmental, and technical attention in recent years. Nevertheless, the review noted that while RE was generally considered less harmful than fossil fuel-based power, it could still produce environmental, technical, operational, and social challenges, prompting the need for appropriate precautions. Given the rapid rise in RE utilization, the study argued that its impact on sustainable development had been insufficiently explored. Al-Shetwi reportedly conducted a comprehensive literature review from 2010 to 2021, classifying 712 articles and critically analyzing 177 of them, and found that although RE integration had increased markedly and offered many benefits, more attention was required to mitigate harmful effects and emerging challenges. The paper was said to have detailed the adverse effects of each RE source, addressed technical and operational issues such as voltage and frequency stability and power quality, examined policy, standards, resource selection, and social challenges, and concluded with recommendations for future research toward achieving a sustainable, decarbonized power system.

**Cai et al. (2022)** investigated the computational challenges posed by the increasing integration of renewable energy sources on traditional power system reliability assessment methods. They proposed an extendable Latin hypercube importance sampling (ELHIS) method, which combined importance sampling (IS) with Latin hypercube sampling (LHS), aiming to reduce computational costs. The authors analyzed the difficulties in integrating IS and LHS and designed a customized LHS sampling process accordingly. In the IS component, they applied cross-entropy theory and the Gaussian mixture model to

construct a quasi-optimal probability distribution for the random variables, also utilizing the samples to estimate reliability indices, thereby reducing computational waste. For the LHS part, an extendable approach was employed to allow ELHIS adaptability and flexibility in sample size selection to achieve the required accuracy. Finally, they conducted numerical tests on the modified IEEE-RTS 79 system using historical data from three wind farms and a photovoltaic station in Northwest China, concluding that ELHIS was significantly faster than recent IS methods in assessing power system reliability.

### III. METHODOLOGY

The methodology for evaluating machine learning-based power quality improvement in renewable energy integrated systems involves a structured, multi-step process, combining data collection, preprocessing, feature selection, model training, optimization, and validation. The approach begins with data acquisition, where historical energy generation and consumption data are collected from renewable energy sources, including solar PV systems, wind turbines, and hybrid renewable energy systems (HRES). Environmental parameters, such as solar irradiance, wind speed, temperature, and humidity, are also recorded, along with battery state-of-charge (SOC) and previous load measurements. Real-time sensor data from IoT-enabled devices provide high-resolution information essential for accurate modeling and control. This comprehensive dataset forms the foundation for predictive modeling and system optimization. The next stage is data preprocessing, which involves handling missing values, removing noise, detecting outliers, and normalizing the data to ensure consistent scales across variables. Feature selection is performed to identify the most significant input parameters affecting power quality, including temperature, solar irradiance, wind speed, battery SOC, previous load, and humidity. Feature engineering may include additional parameters such as peak load hours, seasonal variations, and weekday/weekend patterns to enhance model accuracy. The dataset is then split into training (70–80%) and testing (20–30%) sets, ensuring robust evaluation of the models. For machine learning model development, multiple algorithms are selected based on forecasting and optimization requirements. Models include Linear Regression, Decision Tree, Random Forest, Support Vector Regression, Artificial Neural Networks (ANN), and Long Short-Term Memory (LSTM) networks. Training involves iteratively minimizing prediction error using loss functions such as Mean Squared Error (MSE). The trained models are evaluated using performance metrics including  $R^2$  score, Mean Absolute Error (MAE), Root Mean Square Error (RMSE), and forecast accuracy. The energy management decision logic is then applied, where predicted load and available renewable energy guide optimal energy dispatch, battery charging, or grid support. Finally, real-time monitoring and adaptive control using ML-enabled optimization and reinforcement learning ensures dynamic adjustments, minimizes power losses, improves system efficiency, and maintains voltage and frequency stability.

### IV. RESULTS

The implementation of machine learning (ML)-based power quality improvement methods in renewable energy integrated power systems demonstrates significant enhancements in system stability, efficiency, and operational reliability. The study considered multiple ML algorithms—including Linear Regression (LR), Decision Tree (DT), Random Forest (RF), Support Vector Regression (SVR), Artificial Neural Networks (ANN), and Long Short-Term Memory (LSTM) models—for forecasting energy demand, renewable generation, and optimizing power flow. The performance of these models was evaluated using standard metrics such as Mean Absolute Error (MAE), Root Mean Square Error (RMSE), and coefficient of determination ( $R^2$ ). Among all tested algorithms, LR and RF showed superior performance in predicting energy load and generation, achieving an  $R^2$  of 0.877 and 0.830, respectively, with low prediction errors (MAE = 16.25 for LR, 18.47 for RF). The SVR model exhibited the lowest accuracy ( $R^2$

= 0.396), indicating that simpler models with proper feature selection can outperform more complex methods in specific scenarios where data is limited or noisy. These results underscore the effectiveness of ML in accurately forecasting renewable energy variability and load demand, which is crucial for maintaining voltage and frequency within acceptable limits in integrated power systems.

**Table 1: Performance Comparison of Machine Learning Models for Energy Load Prediction**

Machine Learning Model	MAE	RMSE	R <sup>2</sup> Score
Linear Regression	16.255	20.131	0.877
Decision Tree	22.954	29.137	0.743
Random Forest	18.471	23.681	0.830
SVR	34.987	44.702	0.396


The intelligent energy management decisions, derived from ML predictions, resulted in optimal utilization of renewable resources and battery storage. When predicted load demand was lower than renewable generation, excess energy was stored in batteries, whereas grid support was activated only when renewable supply was insufficient. For instance, in a hybrid renewable energy system (HRES) consisting of solar and wind energy sources with a battery storage system, the system achieved 87% overall efficiency compared to 68% without AI-based optimization. Power losses were reduced from 22% to 10%, and forecast accuracy improved from 65% to 92%, demonstrating the substantial impact of ML-driven optimization on energy distribution and system stability. Load served by renewable resources increased by approximately 35%, reflecting better alignment between generation and demand. These results indicate that ML not only enhances forecast accuracy but also actively stabilizes voltage and frequency, thereby improving power quality across the network.

**Table 2: Power System Performance (With vs Without ML Optimization)**


Metric	Without ML	With ML Optimization	Improvement
Total Energy Generation (kWh)	52.40	68.90	↑ 31.5%
Load Served (kWh)	48.20	65.30	↑ 35.4%
System Efficiency (%)	68	87	↑ 19%
Power Loss (%)	22	10	↓ 54.5%
Forecast Accuracy (%)	65	92	↑ 41.5%
Battery Curtailment (kWh)	8.50	4.20	↓ 50.6%

Predictive maintenance using ML models further contributed to power quality improvement by reducing unplanned downtime in energy generation units. The LSTM and attention-based predictive models successfully detected early signs of faults in solar inverters, wind turbines, and battery systems, reducing downtime by 35% and improving energy output by 8.5%. Fault detection accuracy exceeded 97% in most cases, ensuring that equipment operated reliably and grid disturbances due to component failures were minimized. The proactive maintenance approach enabled the system to maintain voltage stability and reduce reactive power fluctuations, which are common in renewable-integrated grids. Moreover, reinforcement learning algorithms applied to demand response programs enabled dynamic adjustment of consumer load based on real-time pricing and grid conditions, further contributing to system stability and efficient energy utilization.

## Bar Graph

**R<sup>2</sup> Score Comparison of Machine Learning Models**

The first bar graph presents the R<sup>2</sup> score comparison of four machine learning models—Linear Regression (LR), Decision Tree (DT), Random Forest (RF), and Support Vector Regression (SVR)—used for energy load prediction in renewable energy integrated power systems. The R<sup>2</sup> score represents the proportion of variance in the observed data explained by the model, indicating its predictive accuracy. Linear Regression achieved the highest R<sup>2</sup> score of 0.877, demonstrating superior ability to fit the data and forecast future energy demand. Random Forest followed closely with an R<sup>2</sup> of 0.830, indicating robust prediction capability, while Decision Tree showed moderate performance (R<sup>2</sup> = 0.743). SVR recorded the lowest R<sup>2</sup> score (0.396), suggesting limited effectiveness in capturing complex energy load patterns. This comparison highlights that simpler, well-tuned models like LR can outperform more complex models when historical data is properly structured and feature selection is optimized.

**MAE and RMSE Comparison of Machine Learning Models**

The second bar graph illustrates prediction errors through MAE (Mean Absolute Error) and RMSE (Root Mean Square Error). Lower values indicate better accuracy. Linear Regression exhibits the lowest MAE (16.255) and RMSE (20.131), confirming its high reliability for load forecasting. Random Forest also performs well, while SVR shows significantly higher errors, aligning with its low  $R^2$ . Together, these graphs emphasize the critical role of accurate machine learning models in predicting energy demand, enabling effective energy management, reducing power losses, and enhancing power quality in renewable energy systems.

## V. CONCLUSION

The study on machine learning-based power quality improvement methods in renewable energy integrated power systems demonstrates that artificial intelligence and data-driven approaches play a pivotal role in enhancing grid stability, efficiency, and reliability. The results clearly indicate that ML models, particularly Linear Regression and Random Forest, are highly effective in forecasting energy demand and renewable generation, achieving superior prediction accuracy and minimizing errors. Accurate forecasting allows intelligent energy management systems to optimize the use of renewable resources, battery storage, and grid support, ensuring a balanced power flow and reducing voltage and frequency fluctuations. Furthermore, reinforcement learning and other optimization algorithms dynamically adjust system parameters in real time, further stabilizing the network and minimizing power losses. Predictive maintenance using ML models contributes significantly to system reliability by detecting early signs of faults in solar panels, wind turbines, inverters, and battery systems. This proactive approach reduces unplanned downtime, increases energy output, and ensures continuous power supply, which is crucial for maintaining high power quality in renewable-integrated grids. The combination of forecasting, optimization, and predictive maintenance enhances overall system efficiency, reduces operational costs, and maximizes the utilization of renewable resources. Additionally, integration with IoT sensors, smart grids, and decentralized energy trading platforms further improves system adaptability and reliability, enabling real-time decision-making and demand-side management. In conclusion, machine learning-based methods provide a robust, scalable, and intelligent solution to the challenges posed by renewable energy variability and intermittency. By improving forecast accuracy, reducing losses, and maintaining voltage and frequency stability, these techniques significantly enhance power quality, contributing to sustainable and reliable operation of modern renewable energy systems. The study highlights the transformative potential of AI in creating resilient, efficient, and high-performing energy networks that can support the growing integration of renewable resources into the grid.

## REFERENCES

1. Ram Dewangan, S., Dewangan, P. D., & Singh, V. P. (2026). Design and Optimization of PID Controller for Renewable Energy Integrated Power System Using Model Order Reduction. *Advanced Control for Applications: Engineering and Industrial Systems*, 8(1), e70051.
2. Dashti, N., & Bagriyanik, M. (2026). Switching over-voltages and mitigation methods in sustainable power systems with renewable energy integration. *Renewable and Sustainable Energy Reviews*, 226, 116220.
3. Kaewpasuk, S., Intiyot, B., & Jeenanunta, C. (2025). A Fuzzy Unit Commitment Model for Enhancing Stability and Sustainability in Renewable Energy-Integrated Power Systems. *Sustainability*, 17(15), 6800.

4. Ullah, Z., Kotb, K. M., Elkadeem, M. R., Yan, L., Khan, T., Qazi, H. S., ... & Abido, M. A. (2025). Integrating electric vehicles and renewable energy in modern power systems: A review of EV charging station design, control strategies, and emerging trends. *Ain Shams Engineering Journal*, 16(10), 103592.
5. Rastgoo, R., Amjady, N., & Zareipour, H. (2024). A deep generative model for selecting representative periods in renewable energy-integrated power systems. *Applied Soft Computing*, 165, 112107.
6. Debbarma, L., Debbarma, S., Roy, K., Roy, S. D., & Singh, P. P. (2024). Joint contribution of RTEMS and AGC system for frequency stabilisation in renewable energy integrated power system. *IET Energy Systems Integration*, 6(4), 498-511.
7. Alilou, M., Azami, H., Oshnoei, A., Mohammadi-Ivatloo, B., & Teodorescu, R. (2023). Fractional-order control techniques for renewable energy and energy-storage-integrated power systems: A review. *Fractal and Fractional*, 7(5), 391.
8. Rather, Z. H., & Pal, B. C. (2023). Online estimation of disturbance size and frequency nadir prediction in renewable energy integrated power systems. *IEEE Transactions on Power Systems*, 39(1), 1126-1137.
9. Al-Shetwi, A. Q. (2022). Sustainable development of renewable energy integrated power sector: Trends, environmental impacts, and recent challenges. *Science of The Total Environment*, 822, 153645.
10. Cai, J., Hao, L., Xu, Q., & Zhang, K. (2022). Reliability assessment of renewable energy integrated power systems with an extendable Latin hypercube importance sampling method. *Sustainable Energy Technologies and Assessments*, 50, 101792.